

START Ultra SMF A189B4X0_1 85 Ah

According to EN 50342


Electrical specification

Voltage:	12V
Capacity C ²⁰ :	85 Ah
Cold cranking current:	780 A [EN]
Cold cranking current:	465 A [DIN]

Mechanical specification

Dimensional group:	LB4
ETN reference:	585 015 078 SMF
DIN reference:	58515
Dimensions ^A in mm (LxWxH):	310x175x175
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B14
	Colour	Grey

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey



Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Grey

Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	13.60
Acid weight in kg:	5.80
Total battery weight in kg:	19.40

Layout

Hold-down

Separator

Type	PE
------	----

- ^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
- ^{B.} Weight may vary ±5%.