

MONBAT Formula A89B4P0_1 85 Ah

According to EN 50342



Formula

SEALED MAINTENANCE FREE



Electrical specification

Voltage:	12V
Capacity C ²⁰ :	85 Ah
Cold cranking current:	750 A [EN]
Cold cranking current:	450 A [DIN]

Mechanical specification

Dimensional group:	LB4
ETN reference:	585 015 075 SMF
DIN reference:	58515
Dimensions ^A in mm (LxWxH)	310x175x175
Cell Layout:	0
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B4
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V1	E1



Weight^B

Battery weight in kg:	13.40
Acid weight in kg:	5.80
Total battery weight in kg:	19.20

Layout



Hold-down



- ^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
- ^{B.} Weight may vary ±5%.