



Series	4000	Warranty	3 Years
Volts	8	Design	SLI
Cells	4	Plates/Cell	23
Terminal Type	Flag L		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		

Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C		891			
Marine Crank Amps (MCA) 32°F / 0°C		1114			
Reserve Capacity (RC @ 25A)		576 Minutes			
Reserve Capacity (RC @ 75A)		192 Minutes			
Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)	
	105%	100%	75%	50%	

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	319 AH	3.19 A
@ 72 Hour Rate	302 AH	4.2 A
@ 50 Hour Rate	286 AH	5.71 A
@ 20 Hour Rate	240 AH	12 A
@ 15 Hour Rate	228 AH	15.2 A
@ 10 Hour Rate	211 AH	21.12 A
@ 8 Hour Rate	206 AH	25.8 A
@ 5 Hour Rate	190 AH	37.92 A
@ 1 Hour Rate	96 AH	96 A

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F).
Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications

Weight	57.5 kg	127 lbs
Length	686 mm	27"
Width	184 mm	7.25"
Height Incl. Term.	305 mm	12"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

- Plastics are UL94 HB (UL94-V2 available)
- Plastics are impact copolymer rated to ASTM D256, D5420
- Vented design with integral flame arrestor vent caps

Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.07 V	2.00 V	1.92 V	1.75 V
10 HR AH RATE	2.10 V	2.06 V	1.98 V	1.89 V	1.75 V
3 HR AH RATE	2.10 V	2.03 V	1.95 V	1.86 V	1.75 V
1 HR AH RATE	2.10 V	2.01 V	1.93 V	1.84 V	1.75 V



Designed in compliance with applicable BCI, DIN, BS & IEC standards.
Tested in compliance to BCI & IEC standards.



intertek
0122624

Rev.#4 | August 2024